

HONG KONG RADAR 126.3

RNAV (GNSS) BETTY 3A STAR RWY 07L/07C/07R
RNAV (GNSS) BETTY 3B STAR RWY 25L/25C/25R

-
- ELEV, ALT IN FEET
DIST IN NM
BRG ARE MAG
VAR 3°W (2020)**
- HONG KONG
INTL AIRPORT**
- RIVMI**
6 000
4 500
- BETTY 3B**
35.0 342°
- TEDUR**
6 000
- BETTY 3B**
35.0 332°
- BETTY 3A**
26.5 302°
- HH511**
- BETTY 3A**
24.5 316°
- MANGO**
FL 130
AT 280 KIAS
- BETTY**
8.0 345°
- BETTY 3A/B**
165°
345°
- DESCENT REQUIREMENT**
Do not descend without
ATC clearance
- LHM**
6 000
3 000
- Scale 1: 1 000 000**
NM 0 2 4 6 8 10 NM
KM 0 4 8 12 16 KM
- CONTOUR INTERVAL**
2000
1000
500
- MINI SECTOR ALTITUDE**
4300'
4100'
MSA 25NM
ARP
WITHIN HK FIR

CHANGE: New Procedures.

FMC Database Coding Reference for Hong Kong RNAV_(GNSS) STARs**Designator: BETTY 3A Runway 07L / Runway 07C / Runway 07R**

<i>Serial Number</i>	<i>Path Descriptor</i>	<i>Waypoint Identifier</i>	<i>Fly-over</i>	<i>Course/Track (°M)</i>	<i>Magnetic Variation</i>	<i>Distance (NM)</i>	<i>Turn Dir</i>	<i>Altitude (ft)</i>	<i>Speed (KIAS)</i>	<i>Navigation Specification</i>
01	IF	BETTY	-	-	+3.0	-	-	-	-	RNP 1
02	TF	MANGO	-	345	+3.0	8.0	-	@FL130	@280	RNP 1
03	TF	HH511	-	316	+3.0	24.5	-	-	-	RNP 1
04	TF	LIMES	-	302	+3.0	26.5	-	-6000 +3000	-	RNP 1

Designator: BETTY 3B Runway 25L / Runway 25C / Runway 25R

<i>Serial Number</i>	<i>Path Descriptor</i>	<i>Waypoint Identifier</i>	<i>Fly-over</i>	<i>Course/Track (°M)</i>	<i>Magnetic Variation</i>	<i>Distance (NM)</i>	<i>Turn Dir</i>	<i>Altitude (ft)</i>	<i>Speed (KIAS)</i>	<i>Navigation Specification</i>
01	IF	BETTY	-	-	+3.0	-	-	-	-	RNP 1
02	TF	MANGO	-	345	+3.0	8.0	-	@FL130	@280	RNP 1
03	TF	TEDUR	-	352	+3.0	35.0	-	-6000	-	RNP 1
04	TF	RIVMI	-	344	+3.0	13.4	-	-6000 +4500	-	RNP 1

Waypoint and Coordinates

<i>Waypoint Identifier</i>	<i>Coordinates (WGS-84)</i>
BETTY	21 29 10.82N 114 33 31.92E
MANGO	21 36 49.00N 114 30 53.00E
HH511	21 53 32.24N 114 11 31.99E
TEDUR	22 11 18.77N 114 23 51.26E
RIVMI	22 24 03.96N 114 19 09.28E
LIMES	22 06 25.60N 113 46 32.60E